

EVERBRITE, INC.

SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION

PRODUCT NAME: **Everbrite™ Coating**
IDENTIFICATION NUMBER: **EB137**
PRODUCT USE/CLASS: CLEAR PROTECTIVE COATING

DATE PRINTED: 8/27/26

SUPPLIER:
Everbrite, Inc.

MANUFACTURER:
Everbrite, Inc.

11492 Sunrise Gold Circle
Rancho Cordova, CA 95742
+1-916-852-0200 (8:00am-5:00pm PST)

11492 Sunrise Gold Circle
Rancho Cordova, CA 95742
+1916-852-0200 (8:00am-5:00pm PST)

CHEMTREC 24HR EMERGENCY TELEPHONE
+1-800-424-9300 (Inside USA)

CHEMTREC 24HR EMERGENCY TELEPHONE
+1-703-527-3887 (Outside USA)

PREPARER: nbk, PREPARE DATE: 02/04/2016

SECTION 2 - HAZARDS IDENTIFICATION

Classification of substance/mixture

Flammable Liquid, category 4
Skin Irritation, category 2
Eye Irritation, category 2A
Specific target organ toxicity – single exposure, respiratory system, category 3

GHS Label elements, including precautionary statements

Pictogram



Signal Word: Warning

GHS HAZARD STATEMENTS

Combustible Liquid
Causes skin irritation
Causes serious eye irritation
May cause respiratory irritation

GHS PRECAUTION PHRASES

Keep away from heat/sparks/open flames/hot surfaces. – No smoking
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash...thoroughly after handling
Do not eat, drink or smoke when using this product.
Use only outdoors or in well ventilated area
Wear protective gloves/protective clothing/eye protection/face protection
IF ON SKIN: Wash with plenty of water
IF INHALED: Remove person to fresh air and keep comfortable for breathing
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
If skin irritation occurs: Get medical advice/attention.
If skin irritation or a rash occurs: Get medical advice/attention
If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
Store in a well ventilated place. Keep container tightly closed.

Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

CAS NUMBER	CHEMICAL NAME	WT/WT % RANGE
64742-94-5	Naphtha, heavy aromatic	25-50%
111109-77-4	Dipropylene glycol dimethyl ether	25-50%
66028-15-7	High molecular weight polymer coating	25-50%

SECTION 4 - FIRST AID MEASURES

Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient

SECTION 5 - FIRE FIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: no data available

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective firefighting clothing (includes firefighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Refer to section 7, Handling, for additional precautionary measures. Keep personnel out of low areas. Keep unnecessary and unprotected personnel from entering the area. No smoking in area. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Small spills: Absorb with materials such as: Sand. Vermiculite. Collect in suitable and properly labeled containers. Large spills: Contain spilled material if possible. Pump into suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

SECTION 7 - HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes. Wash thoroughly after handling. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Spills of these organic materials on hot fibrous insulations may lead to lowering of the auto ignition temperatures possibly resulting in spontaneous combustion. Keep away from heat, sparks and flame. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Store in the following material(s): Carbon steel. Stainless steel. Phenolic lined steel drums. Do not store in: Aluminum. Copper. Galvanized iron. Galvanized steel. See Section 10 for more specific information.

Storage stability

Steel drums. 24 Month

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	<u>%</u>	<u>ACGIH TLV- TWA</u>	<u>ACGIH TLV- STEL</u>	<u>OSHA PEL- TWA</u>	<u>OSHA PEL- CEILING</u>	<u>OEL Note</u>
Naphtha, heavy aromatic	25-50%	N/E	N/E	N/E	N/E	
Dipropylene glycol dimethyl ether	25-50% 20 ppm		N/E	N/E	N/E	
High molecular weight polymer coating	25-50%	N/E	N/E	N/E	N/E	

FURTHER INFORMATION: Refer to the local country/regional regulatory exposure limits for the workforce.

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

Skin protection

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl").

NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions / specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have

been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

APPEARANCE	: Colorless
PHYSICAL STATE	: LIQUID
BOILING RANGE	: 347-685°F (175-363°C)
VAPOR DENSITY	: Is heavier than air
ODOR	: Mild
ODOR THRESHOLD	: N.E.
EVAPORATION RATE	: Is slower than Butyl Acetate
SOLUBILITY IN H ₂ O	: Not soluble.
FREEZE POINT	: -49- -96°F (-45- -71°C)
SPECIFIC GRAVITY	: 0.9505
VAPOR PRESSURE	: <1.0 mm Hg @ 68°F (20°C)
pH	: N.E.
VOLATILE BY VOLUME	: 74.54%
FLASH POINT	: 145°F (63C)
(SETAFLASH CLOSED CUP)	
AUTOIGNITION TEMPERATURE	: 329°F (165°C)
LOWER EXPLOSIVE LIMIT	: N.E.
UPPER EXPLOSIVE LIMIT	: N.E.
VOC Content (g/l)	: 679 g/l

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

Reactivity: No reactivity hazards known under normal storage and use conditions.

Chemical stability: Stable under normal conditions

Possibility of hazardous reactions: Hazardous polymerization does not occur

Conditions to avoid: Heat, flames and sparks. Product can oxidize at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems.

Incompatible materials: Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Ketones. Organic acids, carbon dioxide (CO₂), carbon monoxide (CO), and irritating fumes and gases.

SECTION 11 - TOXICOLOGICAL PROPERTIES

Information on toxicological effects

Acute Toxicity:

Oral LD₅₀ : N/D

Inhalation LC₅₀ : N/D.

Irritation : Unknown

Corrosivity : Unknown

Sensitization : Unknown

Repeated dose toxicity : Unknown

Carcinogenicity : Unknown

Mutagenicity : Unknown

Toxicity for reproduction : Unknown

If no information is available above under Acute Toxicity, then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS NUMBER</u>	<u>CHEMICAL NAME</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
64742-94-5	Naphtha, heavy aromatic		500 µL/24h mild dermal rabbit >2 ml/kg Skin, rabbit	>590mg/m ³ /4h inhalation, rat
111109-77-4	Dipropylene glycol dimethyl ether	3,300 mg/kg rat	> 2,000 mg/kg rat	>5.25 mg/l 4h rat – no deaths
12-07-2	2-butoxy ethyl acetate	1,800 mg/kg rat	1,500 mg/kg rabbit	ND

Skin corrosion/irritation

Prolonged exposure not likely to cause significant skin irritation.

Serious eye damage/eye irritation

May cause slight eye irritation.

Corneal injury is unlikely.

Sensitization

Skin contact may cause an allergic skin reaction in a small proportion of individuals.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

In animals, effects have been reported on the following organs:

Adrenal gland.

Kidney.

Liver.

Carcinogenicity - No relevant data found.

Teratogenicity

Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

Reproductive toxicity - In animal studies, did not interfere with reproduction.

Mutagenicity

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

Toxicity

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, *Poecilia reticulata* (guppy), static test, 96 Hour, > 1,000 mg/l

NOEC sublethal, *Oncorhynchus mykiss* (rainbow trout), flow-through test, 14 Hour, > 300 mg/l

Acute toxicity to aquatic invertebrates

LC50, *Daphnia magna* (Water flea), static test, 24 Hour, > 1,000 mg/l

Chronic aquatic toxicity

Chronic toxicity to aquatic invertebratesNOEC, *Daphnia magna* (Water flea), semi-static test, 21 d, number of offspring, 10 mg/lLOEC, *Daphnia magna* (Water flea), semi-static test, 21 d, number of offspring, 32 mg/lMATC (Maximum Acceptable Toxicant Level), *Daphnia magna* (Water flea), semi-static test, 21 d, number of offspring, 18 mg/l**Toxicity to soil-dwelling organisms**LC50, *Eisenia fetida* (earthworms), 14 d, survival, > 1,000 mg/kg**Persistence and degradability****Biodegradability:** Material is inherently biodegradable (reaches > 20% biodegradation in OECD test(s) for inherent biodegradability). Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: 18 - 32 %**Exposure time:** 28 d**Method:** OECD Test Guideline 301B or Equivalent

10-day Window: Not applicable

Biodegradation: 25 %**Exposure time:** 28 d**Method:** OECD Test Guideline 302B or Equivalent**Theoretical Oxygen Demand:** 2.17 mg/mg**Photodegradation****Test Type:** Half-life (indirect photolysis)**Sensitizer:** OH radicals**Atmospheric half-life:** 3.8 Hour**Method:** Estimated.**Bioaccumulative potential****Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).**Partition coefficient: n-octanol/water(log Pow):** 0.42 Measured**Bioconcentration factor (BCF):** 4 *Oncorhynchus mykiss* (rainbow trout) 43 d Measured**Mobility in soil**

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process. Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient(Koc): 2 Estimated.**SECTION 13 - DISPOSAL CONSIDERATIONS****Disposal methods:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER.

All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations.

Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

SECTION 14 - TRANSPORTATION INFORMATION**DOT (US)**

Proper shipping name	Not Regulated
UN number	NA
Class	NA
Packing group	NA

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Consult IMO regulations before transporting ocean bulk

Transport in bulk

according to Annex I or II

of MARPOL 73/78 and the IBC or IGC Code

Classification for AIR transport (IATA/ICAO): Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15 - REGULATORY INFORMATION**OSHA Hazard Communication Standard**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Fire Hazard

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Worker and Community Right-To-Know Act:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SECTION 16 - OTHER INFORMATION**Hazard Rating System****NFPA**

RATINGS - HEALTH: 1 FLAMMABILITY: 2 REACTIVITY: 0

Revision

Identification Number: EB137 SDS

Issue Date: 02/04/2016 / Version: 1.1

Reasons for revision: To correct Transportation Information

Previous SDS revision date: 02/04/2016

Version 1.2 Correction of spelling and small errors.

Revision Date: 8/27/26 – Routine review, no changes to composition or hazard classifications.

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references and from external references supplied by our vendors to company.

EVERBRITE ,INC. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer specific SDSs, we are not and cannot be responsible for SDSs obtained from any source other than ourselves. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version.

<END OF SDS>